

INTERNATIONAL STANDARD

ISO
9827

First edition
1994-06-15

Measurement of liquid flow in open channels by weirs and flumes — Streamlined triangular profile weirs

*Mesure de débit des liquides dans les canaux découverts au moyen de
déversoirs et de canaux jaugeurs — Déversoirs carénés à seuil à profil
triangulaire*



Reference number
ISO 9827:1994(E)

Contents

	Page
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Units of measurement	1
5 General requirements	1
5.1 Site selection	1
5.2 Installation conditions	2
6 Maintenance	3
7 Measurement of head	3
7.1 General	3
7.2 Stilling or float well	3
7.3 Zero setting	3
8 Streamlined triangular profile weirs	4
8.1 Specification for a standard weir	4
8.2 Location of head measurement section	4
8.3 Location of tail water level measurement section	4
8.4 Conditions for modular flow	4
9 Discharge calculation	4
9.1 Discharge equation	4
9.2 Coefficients	6
9.3 Limitations	11
9.4 Uncertainty of measurement	11
10 Uncertainties in flow measurement	11
10.1 General	11
10.2 Sources of error	11

© ISO 1994

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland